## <u>Proposed Changes recommended by Rings Scenic Tours</u>

### **PERFORMANCE STANDARDS**

1.1	1.1 PERFORMANCE STANDARDS FOR PERMITTED ACTIVITIES IN PRECINCTS 1 AND 2		
1.	Building Envelope for all buildings associated with, and ancillary to, a permitted activity listed in this DCP	<ul> <li>a) Maximum Height in Precinct 1 and 2: 10m</li> <li>b) Height relative to Precinct boundary - No part of any building shall exceed a height of 3m plus the shortest horizontal distance between that part of the building and the nearest Precinct boundary provided that:         <ol> <li>Buildings may be erected where they encroach on height relative to Precinct boundaries so long as the written approval of the affected property owner(s) is obtained.</li> <li>Front yard in Precinct 1: 15m to Precinct boundary for buildings above-ground, and 10m for buildings below ground. Ground level shall be the level of the existing ground before construction.</li> </ol>             did yards and rear yards in Precincts 1 and 2: 10m to Precinct boundary, provided that -</li></ul>	
		Advice Note: Works in close proximity to all electrical lines can be dangerous. Compliance with the NZECP 34 is mandatory for buildings, earthworks and mobile plant within close proximity to all electrical lines.	
2.	Building Coverage	<ul> <li>a) Total building coverage for Precinct 1 shall not exceed 7.410% of the net site area of Precinct 1 (i.e. a total building area of 6,3426,320m²).</li> <li>b) There is no maximum building coverage for Precinct 2.</li> </ul>	
3.	Visual Form and Appearance of New Buildings	a) Any new buildings shall either reflect the rural vernacular established within the relevant Precinct, being simple in form and appearance and/ or be reflective of the fantasy rural architectural character expressed in existing developments located in Precinct 2.  b) Where responding to the rural vernacular, the following shall apply:  (i) Roofs shall be gable in form only (i.e. no hiproofs) and shall have a pitch of between 20-45 degrees.  (ii) Flat connections between building forms are permitted but shall not exceed 25% of the roof form.  (iii) Lean to roofs are to have a maximum mono pitch roof of 8 degrees.  (iv) Wall claddings shall be continuous. While changes may occur at a recess or visual break point, walls must be done in one cladding form with no changes over the wall surface.  (v) Wall materials shall be one of the following:  • Timber weatherboard;  • Timber board and batten;  • Weatherboard cladding system (similar to Linea);  • Corrugated iron;  • Tray steel;  • Concrete;  • Stone;  • Brick; or  • Plaster masonry.	

c)	If painted, the exterior colour of buildings and structures within
	Precinct 1 shall be restricted to natural, visually recessive colours
	and/or colours that do not contrast with surrounding natural colours
	so that buildings do not appear incongruent with the surrounding
	rural landscape. The following colours, from the BSS 5252 colour
	range or equivalent, meet the requirements of this DCP Performance
	Standard:

Startaura.	
Group	00A01 - A13 inclusive, 02A03, 02A07,
Α	02A11, 06A03, 06A07, 06A11, 08A14,
	10A03 - A11 inclusive 16A03, 16A07,
	16A11, 18A14
Group	04B19 - B29 inclusive, 08B17 - B29
В	inclusive, 10B17 - B29 inclusive, 12B17 -
	B29 inclusive, 18B17 - B29 inclusive,
	22B27, 22B29
Group	06C37 - C40 inclusive, 08C37 - C40
С	inclusive, 10C37, 10C39, 12 C37 - C40
	inclusive, 14 C37 - C40 inclusive, 16 C37 -
	C40 inclusive, 18 C37 - C40 inclusive

- d) Unpainted buildings and structures within Precinct 1 shall be clad in natural materials comprising bricks, stone or timber.
- e) No buildings or structures within Precinct 1 shall have mirrored glazing.

# 4. Landscaping for New Buildings

- a) Within Precinct 1, existing specimen trees and hedging as identified on Mitigation Plan Existing Planting: Precinct 1 Plan C2 Revision R7 dated 30/5/19 that forms part of the DCP as 'to be retained' shall be retained unless removal is required by the siting of new development.
- b) Further development in Precinct 1 shall require the planting of the proposed specimen trees in the locations indicated on Mitigation Plan CXX dated [to be completed] around the Precinct to provide general screening. Proposed specimen trees refer to species that are either Platanus orientalus, Quercus sp., Liquidamber sp., or a species of a similar scale and growth rate New buildings in Precinct 1 shall require specimen tree planting around the Precinct to provide general screening of the new building from outside the Precinct. No specimen tree planting is required along any new buildings frontage that addresses Buckland Road. Specimen tree planting shall occur at a rate of 1 tree per new building plus one additional tree for every 10 linear metres of the buildings perimeter footing. For the avoidance of doubt, buildings addressing Buckland Road shall constitute the primary active frontage of the building.
- c) Should any specimen tree or hedge plant, that is required to be retained, die, or become diseased or damaged such that it is no longer able to provide its mitigation function, it shall be replaced with a specimen of the same species. Replacement shall occur within the first planting season after the loss of the mitigation function is identified.
- d) Soft Landscaping (plants) around all new buildings shall extend a minimum of two metres beyond the building envelope on at least three sides of the building and shall comprise grasses, shrubs and/or groundcovers.
- e) All planting shall be implemented within the first planting season (March to May or September to November) after any buildings and associated site works are completed.

	T
	Advice Note: Works in close proximity to all electric lines can be
	dangerous. Compliance with the NZECP 34 is mandatory for buildings,
	earthworks and mobile plant within close proximity to all electric lines.
	Advice Note: Compliance with the Electricity (Hazards from Trees)
	Regulations 2003 is also mandatory for tree trimming and planting. To
	discuss works, including tree planting, near electrical lines, especially
	within 20m of those lines, contact the line operator.
5. Landscaping	a) All car parking areas within Precinct 1 shall be screened from Buckland
of Car Parking	Road by earth mounding and/or planting to a minimum height of
Areas	1.2m.
	Advice Note: Compliance with the Electricity (Hazards from Trees)
	Regulations 2003 is also mandatory for tree trimming and planting. To
	discuss works, including tree planting, near electrical lines, especially
	within 20m of those lines, contact the line operator.
6. Access	a) Precinct 1 shall have no more than two vehicle crossings to Buckland
	Road. The <u>vehicle</u> crossings shall be located in accordance with the
	DCP.
	b) Access to Precinct 2 shall be obtained via one vehicle crossing to
	Buckland Road.
	c) The vehicle crossings shall be designed, formed, constructed and
	maintained in accordance with the MPDC Development Manual 2010.
	d) The vehicle crossings shall comply with the minimum sight distances
7 Deed eefet.	contained within the MPDC Development Manual 2010.
7. Road safety,	a) A minimum of 379 car parking spaces shall be provided within
Trip	Precinct 1. The car parking spaces and associated access and
Generation,	manoeuvring spaces shall be formed, surfaced, line marked and
Car Parking,	maintained in accordance with the MPDC Development Manual 2010.
Loading,	b) Grassed areas suitable for all-weather parking in summer (November
Formation	to March) shall be provided and maintained for overspill parking
and	within Precinct 1. The grassed areas shall be of sufficient area to
Manoeuvring	ensure that there is a minimum total of 450 car parking spaces
	provided within Precinct 1.
	c) A sufficient area shall be formed, constructed and maintained in
	accordance with the MPDC Development Manual 2010 to
	accommodate a minimum of 5 bus parking spaces within Precinct 1.
	d) In addition to the parking requirement in 1.1.7a) and 1.1.7b) above, a
	minimum of 1 car parking space shall be provided and maintained in
	accordance with the MPDC Development Manual for each Hobbiton Movie Set Visitor Accommodation unit.
	e) There are no minimum car parking requirements for Precinct 2.
	f) A dedicated on-site loading facility to accommodate heavy vehicles
	(being articulated vehicles or truck and trailer) shall be provided and
	maintained in both Precinct 1 and Precinct 2, in accordance with the
	MPDC Development Manual.
	g) Parking areas and loading spaces shall be clearly signposted at the
	road frontage in accordance with the NZ Transport Agency's Traffic
	Control Devices Manual, except that the signs may comprise Hobbiton
	colours and include Hobbiton branding.
	h) Parking and loading spaces shall be provided so that no reverse manoeuvring onto or from Buckland Road is needed. The
	_
	manoeuvring area provided shall take into account the type of vehicle anticipated.
	·
	-
	the Hobbiton Movie Set Development Concept Plan (DCP) site shall be

- parked within Precincts 1 and 2. No vehicles shall be parked in the road reserve.
- j) The owner and/or <u>Site</u> Operator of the DCP site shall be responsible for the maintenance costs of the work listed below on an ongoing basis:
  - Works located on any part of the site that is owned, leased or occupied by the owner/ operator of the DCP;
  - Works outlined in the Signage Strategy; and
  - Roading improvements shown on Bloxam Burnett and Olliver Drawing No's 144150/00/P/101 to 144150/00/P/110 Revision BC dated 24 November 2017 30 May 2019 and 144150/00/P/111 to 144150/00/P/115 Revision A dated 30 May 2019.

**Advice note**: Council will undertake all maintenance works for the roading improvements in the road reserve and invoice the <u>Site</u> Operator <u>/ landowner</u> following the works being carried out.

- k) Trip generation resulting from all activities undertaken at the DCP site shall not exceed a daily average of 2,100 trips calculated over a 7 day period.
- I) The Site Operator shall accurately monitor and record daily, weekly, monthly and annual trip generation by vehicle type (i.e. split between light vehicles and heavy commercial vehicles) and shall make the records available to the Matamata-Piako District Council as part of the Site Management and Monitoring Plan and upon request.
- m) k) The Site Operator shall at all times use all reasonable endeavours and shall take such steps as are practicable to:
  - discourage Hobbiton traffic from using the section of Buckland Road west of the DCP site; and:
  - encourage Hobbiton traffic to use the eastern section of Buckland Road.

Such measures shall include but shall not necessarily be limited to:

- Sending out annual notices to all tour bus operators reminding them that the recommended travel route is via the eastern end of Buckland Road and that Rangitanuku Road should be avoided.
- (ii) Placing advisory information on the Site Operator's website.
- (iii) Printing advisory information on booking tickets.
- (iv) Maintaining advisory signage at the Precinct 1 vehicle exit.
- (v) Requesting internet-based mapping sites to direct Hobbiton traffic via the eastern end of Buckland Road.
- n) I) The Site Operator shall take such steps as are practicable to avoid pedestrians stepping within the Buckland Road reserve at the Precinct 1 frontage. Such measures shall include but shall not necessarily be limited to:
  - (i) Displaying advisory signage at the Precinct 1 boundary with Buckland Road.
  - (ii) Creating and sign posting alternative safe locations outside of the Buckland Road reserve for photo opportunities for visitors.
  - (iii) Constructing barriers to prevent pedestrians crossing Buckland Road.
- Within six months of Plan Change 50 (Hobbiton) becoming operative, improvements to provide 114 metre stopping sight distance (SSD) from vehicle crossings to 385 and 399 Buckland Road shall be designed and constructed.

# 8. Visitor Numbers

- Total visitor numbers during Movie Set Tour Hours including patrons of Themed and Non-themed Events shall not exceed 3,500 people per day.
- b) The Site Operator shall accurately monitor and record visitor numbers both during and outside of Movie Set Tour Hours, and shall make the records available to the Matamata-Piako District Council as part of the Site Management and Monitoring Plan and upon request. The records to be provided related to Movie Set Tour Hours shall be:
  - Daily visitor numbers (movie set tour tickets sold)
  - Daily number of bookings
  - Daily number of visitors booked in groups of 8 or more
  - Daily number of staff

#### 9. Noise

a) The noise level from site activities other than the exclusions listed in DCP Performance Standards 1.1.9 b), c) and d) below, as measured at any point within the notional boundary of any rural dwelling located outside the Hobbiton Movie Set Development Concept Plan (DCP) area and existing at [insert date of plan change notification] shall not exceed the following:

7.00am to <u>10</u> 8.00 pm	50 dB L <sub>Aeq</sub>
108.00 pm to 7.00am	40 dB L <sub>Aeq</sub> and 70 dB
	L <sub>Amax</sub>

- b) Seasonal or temporarily intermittent noise resulting from agriculture and forestry activities (e.g. crop spraying, agriculture or forestry harvesting, frost control etc) consistent with the predominant character of the Rural zone, are permitted provided that:
  - The activity is conducted in accordance with good management practice; and
  - ii) Machinery is operated in accordance with manufacturers' specifications.

This exclusion does not include rural operations such as the distribution of industrial factory by-products.

- c) Up to 12 themed outdoor movie screening events that exceed the noise levels in Performance Standard 1.1.9 a) above are permitted to 11.0010.30 pm during daylight savings time and to 10.00 pm at all other times in any calendar year, with no more than two events (outdoor movie screening or outdoor amplified music/concert events) in a seven-day period, and no more than three events in a calendar month. The events shall not exceed 55 dB LAeq when measured at any point within the notional boundary of any rural dwelling located outside the DCP area and existing at [insert date of plan change notification].
- d) Up to 6 themed outdoor amplified music /concert events that exceed the noise levels in Performance Standard 1.1.9 a) above are permitted in any calendar year, with no more than two events (outdoor movie screening or outdoor amplified music/concert events) in a seven-day period, and no more than three events in a calendar month. The events shall:
  - Not exceed six hours duration (excluding sound testing and balancing on the day of the event);
  - (ii) Not exceed <u>65</u><del>60</del>dB L<sub>Aeq</sub> as measured at any point within the notional boundary of any rural dwelling located outside the DCP area and existing at [insert date of plan change notification]; and

- (iii) End by 10.30pm during daylight savings and by 10.00pm at all other times of the year; and
- (iv) Have a period of sound testing and balancing undertaken on the day of the event between 9.00am and 3.00pm. The noise from the testing shall not exceed 55 dB L<sub>Aeq</sub> as measured at any point within the notional boundary of any rural dwelling located outside the DCP area and existing at [insert date of plan change notification]. The cumulative sound testing period shall not exceed 1 hour.
- e) Written notice shall be provided to the occupiers of all properties, within a 3km radius of the Precinct where any outdoor screening or amplified music / concert event is being held, a minimum of fourteen days prior to the event. The written notice shall include the following details:
  - The date and time of the event; and
  - The name and mobile phone number of a contact person who will be available to respond to any enquirers prior to, during and after the event.
- f) The Site Operator shall accurately monitor and record the date of events referred to in c) and d) above, start and finish times, number of patrons that attended the events, notices served, and monitoring undertaken to show compliance with the noise levels and shall make the records available to the Matamata-Piako District Council as part of the Site Management and Monitoring Plan and upon request.
- g)f) A single noise management plan shall be prepared for all amplified music/concert and outdoor movie events. It shall be submitted to Council for certification in a technical capacity that the matters listed below have been addressed, at least 10 working days prior to the first event and shall detail:
  - The applicable noise limits;
  - How noise from the events will be managed and controlled to comply with the limits in 1.1.9c) and 1.1.9d) above;
  - Noise monitoring locations and methodology;
  - A list of neighbours who have been consulted and a summary of the consultation;
  - How any complaints will be recorded and managed; and The noise management plan shall be implemented for the duration of all amplified music/ concert and outdoor screening events.
- h)g) Monitoring of sound levels during the first occurrence of each event type listed in Performance Standards 1.1.9c) and d) above shall be carried out at any point within the notional boundary of the closest neighbouring dwelling to that event, and in response to any complaints of these event types should they arise. Monitoring shall be undertaken at five-minute intervals throughout the event (including any sound testing) by a person qualified to undertake noise measurements. If the noise limits are not complied with, the following similar type of event shall be monitored and the noise management plan updated if required and the updated version certified by Council, until compliance is achieved. In each case a report of the monitoring results shall be completed submitted to Council within 10 working days of the event(s).
- ih) If consent is not given to monitor within the notional boundary of the closest neighbour, the noise shall be monitored at a representative location and the method adopted to determine compliance with the noise limits included in the report to the Council.

	Tan and the state of the state
	<ul> <li>iji) All Sound levels shall be measured and assessed in accordance with the requirements of NZS 6801:2008 "Acoustics – Measurement of Environmental Sound" and New Zealand Standard NZS 6802:2008 "Acoustics – Environmental Noise".</li> <li>kji) Construction noise from the site shall comply with NZS 6803:1999 "Acoustics – Construction Noise".</li> </ul>
10. Lighting and	a) At no time between 7.00am and 10.00 pm shall any outdoor lighting
Glare	be used in a manner that causes an added illuminance in excess of
Sidic	125 lux, measured horizontally or vertically at the boundary of
	Buckland Road or any Rural zoned site located outside the Hobbiton
	Movie Set Development Concept Plan (DCP) area.
	b) At no time between the hours of 10.00 pm and 7.00am, or between
	the hours of 11.00pm and 7.00am when an amplified music/ concert
	or outdoor movie screening event is being held, shall any outdoor
	lighting be used in a manner that causes:
	i) An added illuminance in excess of 10 lux measured horizontally
	or vertically at the boundary of Buckland Road or at any window
	of an adjoining building within the Rural zone located outside
	the DCP area.
	ii) An added illuminance in excess of 20 lux measured horizontally
	or vertically at any point along any Rural zone boundary located
	outside the DCP area.
	c) Where measurement of any added illuminance cannot be made
	because any person refuses to turn off outdoor lighting,
	measurements may be made in locations of a similar nature which are
	not affected by such outdoor lighting.
	d) The outdoor lighting within the DCP area shall be so selected, located,
	aimed, adjusted and screened as to ensure that glare resulting from
	the lighting does not cause a significant level of discomfort to user of
	Buckland Road or to any occupants of any adjoining Rural zoned site
	located outside the DCP area. For the purposes of this rule the
	discomfort level is defined as one that can be detected and
	determined to be a nuisance by an appropriately experienced Council
	officer who is able to apply the frequency, intensity, duration and
	offensiveness to their observations and who is able to report these
	accurately.
11. Street	a) Prior to the commercial use of any Hobbiton Movie Set Visitor
Lighting	Accommodation within Precinct 1, a single street light shall be
42.5	installed opposite the Precinct 1 entry access.
12. Signage	a) The following signs related to permitted activities established within
	Precincts 1 and 2 for the advertisement or identification of the
	established permitted activities:
	i) Signs attached to or forming part of a building: a maximum total
	area of 16m <sup>2</sup> for Precincts 1 and 2 combined.
	ii) Free standing signs: a maximum total area of 16m <sup>2</sup> for Precincts
	1 and 2 combined.  h) From standing signs within Procinct 1 shall only be visible external to
	b) Free-standing signs within Precinct 1 shall only be visible external to
	the Precinct from Buckland Road where the road runs adjacent to the
	northern boundary of the Precinct and 20 metres beyond.
	Advice note: For the avoidance of doubt: there are no controls on
	signage only internally visible to the Hobbiton DCP area or for signs
	whose sole purpose is to direct traffic within a Precinct.
	c) Health and Safety signs to meet legislative requirements: no size
	maximum.  d) The size of letters on signs directed at passing traffic on Buckland
	d) The size of letters on signs directed at passing traffic on Buckland
L	Road shall have a minimum height standard of 150mm.

	<del>,</del>
	e) Directional signs on local roads and state highways may be erected
	for Hobbiton Movie Set provided that the written consent of the
	Matamata-Piako District Council or NZ Transport Agency,
	respectively, is obtained. Directional signs erected under this
	Performance Standard shall not be subject to the DCP Signage
40 =	Performance Standards 1.1.12 a), b), c) and d) above.
13. <del>Themed</del> <del>Events</del>	a) Events involving up to 1,000 patrons within Precincts 1 and 2 where no more than 500 patrons will arrive and depart the event by private
<del>(including</del>	car/mini-van: more than one event may be held at any one time
those events provided for	provided the total number of patrons for the events does not exceed 1,000.
in 1.1.9 c) and	b) Events held during Movie Set Tour hours: the operator shall manage
1.1.9d)); and Non-themed	Events and Movie Set Tour visitor numbers so that total parking demand within Precinct 1 does not exceed:
Events	<ul> <li>the all-weather surface parking capacity available on site at the time of the event</li> </ul>
	c) The operator of the events must maintain records of all events, including:
	Date, time, Precinct and type of event;
	The number of patrons in attendance at the event and on the site
	as a whole;
	The method of arrival and departure for all patrons for events
	involving more than 500 patrons; <u>and</u>
	Records of written notice to neighbours for events involving
	fireworks displays where the fireworks are not classified as 1.3G,
	1.4G and 1.4S under the Hazardous Substances and New
	Organisms (HSNO) Act and corresponding regulations.;
	<ul> <li>These records shall be supplied to Council as part of the Site</li> </ul>
	Management and Monitoring Plan and upon request.
14. Fireworks	a) Fireworks displays shall use fireworks that meet classification 1.3G,
Displays	1.4G and 1.4S under the HSNO and corresponding regulations;
	<u>purchased from a New Zealand retailer in accordance with the Code</u>
	of Practice for Retail Fireworks, 2008.
	b) For events involving fireworks displays where the fireworks are not
	classified as 1.3G, 1.4G and 1.4S under the HSNO and corresponding
	regulations and are not able to be purchased from a New Zealand
	retailer in accordance with the Code of Practice for Retail Fireworks
	2008, written notice shall be provided to the Matamata-Piako District
	Council and the occupiers of all properties located within a 3km radius
	of where the fireworks display is being held. The written notice shall
	be provided a minimum of 14 days prior to the event and include the
	following details:
	The date and approximate time of the planned fireworks display;
	and
	The name and mobile phone number of a contact person who will
	be available to respond to any enquires prior to, during and after the event.
	c) No fireworks displays shall be held between 1 August and 31 October
	in any calendar year.
	d) All fireworks displays shall be limited to the use of fireworks that meet
	classification 1.3G, 1.4G and 1.4S under the Hazardous Substances
	and New Organisms (HSNO) Act and corresponding regulations;
	purchased from a New Zealand retailer in accordance with the Code
	of Practice for Retail Fireworks, 2008.
	Of Practice for Retail Fireworks, 700x.

e) The noise from fireworks must not exceed 40dB LAeq and 70dB LAeq at any point within the notional boundary of any rural dwelling

	Jacobad autoida tha Habbitan Mauis Cat Devalarment Concert Plan
	located outside the Hobbiton Movie Set Development Concept Plan
45 Santharania	(DCP) area and existing at [insert date of plan change notification].
15. Earthworks	a) Cut and fill earthworks and imported cleanfill activities shall be
Cleanfill	located outside the front, side and rear yards as defined in performance standard 1.1.1, except that this performance standard
Cleanin	shall not apply to earthworks necessary for building works authorised
	by a building consent and the area of the earthworks is no more than
	150% of the area of the building.
	b) Imported cleanfill shall not exceed the depositing of more than
	2,000m <sup>3</sup> of material (as measured compacted in place).
	c) All vehicle movements associated with earthworks, construction
	and/or development shall not track dirt and loose material onto the
	road carriageway. Any material which may inadvertently deposit on
	the road must be washed or swept clear of the road carriageway in a
	timely manner so that there is no hazard to the travelling public.
	g passes
	Advice Note: Earthworks should be undertaken in accordance with the
	Waikato Regional Council's "Erosion and sediment control: guidelines for
	soil disturbing activities", Report: TR 2009/02.
	Advice Note: Earthworks must comply with the land disturbance rules in
	the Waikato Regional Plan or resource consent must be obtained from the
	Waikato Regional Council.
	Advice Note: Works in close proximity to all electrical lines can be
	dangerous. Compliance with the NZECP 34 is mandatory for buildings,
	earthworks and mobile plant within close proximity to all electrical lines.
	Advice Note: The location of underground infrastructure should be
	identified prior to works commencing to ensure that infrastructure is not
	accidently dug into and to avoid serious injury or a costly service
	interruption. Information on the location of underground pipes and cables
	can be obtained through the "Dial Before You Dig" service found online at
	http://www.beforeudig.co.nz/#.
	Advice Note: Where works are proposed in close proximity to any
	overhead or below ground electrical line, individuals are advised to
	contact the line operator to discuss works.
<del>16.</del>	a) A maximum of 86 visitors per night are permitted in the area marked
Accommodation	for "Hobbiton Movie Set Visitor Accommodation" located in Precinct 1
	as shown on the DCP.
	b)—A maximum of 30 self-contained mobile camping vehicles are
	permitted per night in the area marked for "Hobbiton Movie Set
	Overnight Park-Over Camping" located in Precinct 1 as shown on the
	<del>DCP.</del>
	c) The Site Operator shall accurately monitor and record the number of
	visitors and self-contained mobile camping vehicles using the
	accommodation facilities referred to in a) and b) above and shall make
	the records available to the Matamata-Piako District Council as part of
	the Site Management and Monitoring Plan and upon request.
17. Community	a) The Site Operator shall provide all owners and occupiers of properties
liaison	with frontage to the full length of Buckland Road and the Matamata-
	Piako District Council with an opportunity to meet on at least an
	annual basis.
	b) The procedure to enable the community liaison referred to in a)
	above to take place and any changes to the procedures over time shall
	be documented in the Site Management and Monitoring Plan.

18. Site	a) Within three months of Plan Change 50 (Hobbiton) becoming
Management and	operative, the Site Operator shall submit a Site Management and
Monitoring	Monitoring Plan ("SMMP") to the Matamata-Piako District Council for
	certification in a technical capacity as to compliance with the matters
	in b) below.
	b) The SMMP shall outline:
	(i) the day-to-day procedures to ensure that the performance
	standards in this DCP are being complied with;
	(ii) the day-to-day procedures to ensure that the monitoring
	required under the performance standards in this DCP are being undertaken;
	(iii) the format and frequency (being no less than six-monthly unless
	otherwise agreed to by the Council in writing) for reporting
	monitoring results to the Matamata-Piako District Council in a
	timely manner that will enable the Matamata-Piako District
	Council to readily ascertain whether the performance standards
	are being complied with.
	c) The Site Operator shall annually, by no later than 30 June, review the
	SMMP in consultation with the Matamata-Piako District Council and
	make amendments to the SMMP (if required) to give effect to the
	findings of the review.
	d) The Site Operator shall at all times adhere to the procedures outlined
	in the SMMP and any amendments thereto resulting from the annual
	<del>review.</del>
	e)—The cost of any work incurred by the Matamata-Piako District Council
	in assessing and monitoring compliance of permitted activities on the
	DCP site with applicable standards and rules shall be at the cost of the
	Site Operator, based on a fair and reasonable assessment by the
	Matamata-Piako District Council of the costs it incurs in carrying out
	such work.
1 <u>6</u> 9. Domestic	a) The facilities shall be associated with Hobbiton.
wastewater	b) The operation of the facilities shall not result in odour that is
treatment	objectionable to the extent that it causes an adverse effect at or
systems and	beyond the boundary of the DCP site.
disposal areas/	c) A minimum 10m width riparian planting margin shall be provided
Stormwater	around the stormwater management devices adjacent to Precinct 1,
treatment and	with the riparian planting comprising locally appropriate eco sourced
attenuation	native species at a density of 5,100 stems/ha (1.4m centres).
facilities	